



✉ info@stshygiene.com.au

REA 18kW Dry Saturated Steam Generators

stshygiene.com.au

Deal for cleaning, sanitising and degreasing of all types of equipment and surfaces in the Food Manufacturing and Engineering Industries. Available with 4 or 5 pin plug.

Deep Clean with Steam

REA 18kW Dry Saturated Steam Generators – Heavy duty professional

REA S18E



REA Special 2



Technical specifications of REA 18kW steam generators

Model name	S18E*	Special 2
Power Supply	400V /28A/ 50Hz	400V /28A/ 50Hz
Power	3-phase 18kW	3-phase 9kW
Steam Production	30 kg/hour	30 kg/hour
Temperature in boiler	188°C	188°C
Temperature at nozzle	150°C	150°C
Bar of Pressure	12	12
Start-up time	4 minutes	4 minutes
Water Tank Capacity	25 lt	100 lt
Water Consumption	30 lts/hr	30 lts/hr
Water Indicator	Yes	Yes
Detergent Tank	10 lt	10 lt
Detergent Indicator	Yes	Yes
Adjustable Detergent Mixer	No	Yes
Standard Hose Length	6 mt	6 mt
Maximum Hose Length	12 mt	12 mt
Electrical Cable Length	10 mt	10 mt
Control Handle / Control Panel	Analogue 12V / 24 V	Digital 12V / 24 V
Markings and Certifications	CE – PED – IPX 5	CE – PED – IPX 5
Vacuum	No	Socket for Vacuum 057 operated from the control handle
Weight	165 kgs	165 kgs
Dimensions in cms	L128 x W745 x H102	L128 x W745 x H102
Body	Stainless steel (AISI 304)	Stainless steel (AISI 304)
Functions		
Selected from the Control Handle	<ul style="list-style-type: none"> <input type="radio"/> Steam only <input type="radio"/> Steam and detergent 	<ul style="list-style-type: none"> <input type="radio"/> Steam only <input type="radio"/> Steam and detergent <input type="radio"/> Steam and water <input type="radio"/> Steam, detergent and vacuum <input type="radio"/> Steam and vacuum <input type="radio"/> Vacuum