





Compact 9 (without vacuum)



Super (with vacuum)



Model name	Compact 9	Super
Power Supply	400V /14A/ 50Hz	400V /14A/ 50Hz
Power	3-phase 9kW	3-phase 9kW
Steam Production	15 kg/hour	15 kg/hour
Temperature in boiler	188°C	188°C
Temperature at nozzle	150°C	150°C
Bar of Pressure	12	12
Start-up time	4 minutes	4 minutes
Water Tank Capacity	15 lt	50 lt
Water Consumption	15 lts/hr	15 lts/hr
Water Indicator	Yes	Yes
Detergent Tank	15 lt	1.4 lt
Detergent Indicator	Yes	Yes
Adjustable Detergent Mixer	No	Yes
Standard Hose Length	4 mt	4 mt
Maximum Hose Length	10 mt	10 mt
Electrical Cable Length	8 mt	8 mt
Control Handle / Control Panel	Analogue 12V / 24 V	Digital 12V / 24 V
Markings and Certifications	CE - PED - IPX 5	CE - PED - IPX 5
Vacuum	No	Socket for Vacuum 057 operated from the control handle
Weight	60 kgs	80 kgs
Dimensions in cms	L62 xW46 x H89	L88 x W54 x H91
Body	Stainless steel (AISI 304)	Stainless steel (AISI 304)
Functions Selected from the Control Handle	Steam only	Steam only
	Steam and detergent	Steam and detergent
		Steam and water
		Steam, detergent and vacuum
		Steam and vacuum
		O Vacuum